

DATASHEET: PI-30

PIPE INTRUDER TOOL SPECIFICATION 30"	
Overall length	4000 mm
Weight	Ca. 3000 kg
Max flow rate in water without resistance	95 m ³ /hr (Increased friction will reduce flow rate)
Max water depth	350 m water depth (35 Bars)
Bend radius	Min 1.5 x D bend (Min 5 D with above 60% of bore off takes)
Constrictions	ID changes, full bore Tees
Environmental working temperature	1-40 °C
Working conditions	In liquid, liquids other than water to be evaluated based on viscosity and temperature



Revision	Description	Date	Produced	Checked	Approved
00	Issued for use	2008-09-14	SGO	JCH	BJ

Note:
 AGR PipeTech AS build custom made tooling for internal tethered inspections, tooling parameters will be taken into consideration based on piping dimensions and requirements

Confidential Property:
 The information contained in this document is the sole property of AGR PipeTech AS.
 The Document shall not be copied or communicated without consent from AGR PipeTech AS



AGR PipeTech AS – P.O. Box 163, Smålonane 12-14, N-5342 STRAUME, NORWAY
 Tel: +47 56 31 60 00, Fax: +47 56 31 60 01
 E-mail: pipetech@agr.com – www.agr.com
 NO 986571116 MVA